



GUIL®



- DGVV Regulation 17 & 18
- DGVV Rule 115-002
- DIN 5690-1
- 2006/42/CE



REF.	MAXIMUM HEIGHT ALTURA MÁXIMA	MAXIMUM LOAD CARGA MÁXIMA	HEIGHT STOWED ALTURA PLEGADA
ULK 400	5,00 m 16.40 ft	250 Kg 551 lb	1,70 m 5.58 ft
ULK 500	6,00 m 19.70"	220 Kg 485 lb	1,70 m 5.58 ft
ULK 400 PLUS	5,00 m 16.40 ft	250 Kg 551lb	1,98 m 6.50 ft
ULK 500 PLUS	6,50 m 21.32"	230 Kg 507 lb	1,98 m 6.50 ft
ULK 600	6,00 m 19.70 ft	320 Kg 705 lb	1,63 m 5.35 ft
ULK 650	6,50 m 21.32 ft	350 Kg 772 lb	1,99 m 6.53 ft
ULK 700	5,00 m 16.40 ft	380 Kg 838 lb	1,98 m 6.50 ft
ULK 800	8,00 m 26.25 ft	300 Kg 661 lb	1,99 m 6.53 ft
ULK 600XL	6,00 m 19.70 ft	350 Kg 772 lb	1,63 m 5.35 ft
ULK 650XL	6,50 m 21.32 ft	400 Kg 882 lb	1,99m 6.53 ft
ULK 800XL	8,00 m 26.25 ft	350 Kg 772 lb	1,99 m 6.53 ft



LINE ARRAY



TRUSS



LED SCREEN